






Pits & Associated Products



Pits & Associated Products

AUSTRALIAN STANDARD AS3996:2006

CLASS RATING	NOMINAL WHEEL LOADING	SERVICEABILITY DESIGN LOAD	ULTIMATE DESIGN LOAD	TYPICAL USES
 <p>RESIDENTIAL Will withstand 1.5 Tonne Wheel</p>	N/A	N/A	N/A	<p>A non-rated drainage channel designed for use in residential applications such as pathways and driveways.</p> <p><i>Will withstand 1.5 Tonne Wheel Loading</i></p>
 <p>CLASS A • Pedestrians • Cyclists</p>	330 KG	6.7 KN	10 KN	<p>Precincts (including footways) accessible only to pedestrians & pedal cyclists, closed to any other traffic.</p>
 <p>CLASS B • Passenger Vehicles • Light Commercial</p>	2670 Kg	53 KN	80 KN	<p>Areas (including driveways & footpaths) accessible to passenger & light commercial vehicles.</p>
 <p>CLASS C • Slow Moving Vehicles • Heavy Commercial Vehicles</p>	5000 KG	100 KN	150 KN	<p>Malls and areas open to slow moving and heavy commercial vehicles.</p>
 <p>CLASS D • Highways • Fast Moving</p>	8000 KG	140 KN	210 KN	<p>Carriageways & roads subject to fast moving heavy commercial vehicles.</p>